



6722W

MINI HANDSFREE BM MONITOR, VIP



Handsfree colour monitor for VIP system. 4.3" / 16:9 colour screen. 480x272 pixel resolution. H264 video format. All the main functions and programming operations can be performed from a graphic menu that can be navigated using the function keys. Equipped with 8 soft-touch keys: audio activation key with LED to signal incoming calls, lock-release key with door open indicator LED, Privacy function key with Led indicating ringtone excluded and Doctor function enabled, 4 programmable keys and 1 menu access key. Equipped with 3 programmable inputs. Adjustable backlight brightness and key feedback volume. Powered by PoE as standard or from VIP Comelit switches and power supply units. Includes induction loop with T position for users wearing hearing aids and answerphone function. Dimensions: 115x160x22 mm.

AWARDS





6722W

MINI HANDSFREE BM MONITOR, VIP

GENERAL DATA

Product height (mm):	160
Product width (mm):	115
Product depth (mm):	22
Product weight (g):	540
Product color:	White RAL9003
Material:	Plastic, ABS
Wall mounting:	Yes
Desk base-mounted:	Yes, with a dedicated accessory

COMPATIBLE SYSTEMS

ViP:	Yes
------	-----

DISPLAY FEATURES

Size (inches):	4.3
Aspect Ratio:	16:9
Resolution (pixels):	480x272
OSD menu:	Yes

AUDIO FEATURES

Type:	Hands-free
Induction loop function:	Yes
Microphone:	6mm (ø), omnidirectional
Loudspeaker:	36mm (ø), 8 ohm, 1W

ELECTRICAL CHARACTERISTICS

Type of power supply:	PoE
PoE power supply:	Standard IEEE 802.3af, Comelit PoE (56VDC)
Stand-by absorption (W):	1.65
Maximum absorption (W):	2.53

HARDWARE FEATURES

Type of buttons:	Capacitive
Service buttons:	Lock-release, Answer, Silent (Privacy), Menu, Messages, Door open
No. of programmable buttons for additional functions:	4
Terminals:	- IN1 IN2 IN3
Number of inputs:	3
Communication ports:	RJ45 (Ethernet)



6722W

MINI HANDSFREE BM MONITOR, VIP

SETTINGS

Loudspeaker volume:	Yes
Ringtone volume:	Yes
Screen backlight:	Yes

NETWORK AND COMMUNICATION PROTOCOLS

Type of LAN network:	Ethernet 10/100 Mbit/s, IEEE 802.3, IEEE 802.3u (Fast Ethernet)
IP address assignment:	Auto IP, DHCP, Static

ENVIRONMENTAL AND COMPLIANCE FEATURES

IP protection degree:	IP30
Operating temperature (°C):	5 ÷ 40
Operating humidity (RH max - %):	25 ÷ 75
Environmental class:	I
Compliance and Certifications:	RoHS II - 2011/65/UE (EN 50581:2012), EMC 2014/30/UE (EN 61000-6-1:2007 , EN 61000-6-3:2007+A1:2011)

MAIN FUNCTIONS

Door opener:	Yes
Self-ignition:	Yes
Intercom calls:	Yes
Actuator control:	Yes
CPS call:	Yes
Outside door call input:	Yes
"Silent" mode (Privacy):	Yes
Video memory:	Yes
Door opening on call (Doctor):	Yes
Automatic answer (handsfree):	Yes
Door open signaling:	Yes
Call forwarding:	Yes
Multiple address:	Yes
Customizable ringtone:	Yes
Date/time display:	Yes
Sending alarm calls:	Yes
Sending e-mail on event:	Yes
Receiving VIP messages:	Yes
ViP anti-theft function:	Yes



6722W

MINI HANDSFREE BM MONITOR, VIP

ACCESSORIES



6711WV

ADAPTER PLATE FOR MINI HANDSFREE

Adapter plate to finish the installation of the Mini Handsfree monitor in case of replacement of flush-mounted or wall-mounted Planux, Smart and Icona monitors. White color. Dimensions: 170x220x3 mm.



6720V

Access. cables external passage for MINI HF. ViP

Wall bracket for ViP system hands-free Mini monitor; allows through-routing of external cables.



6732V

DESK BASE FOR HANDS-FREE MINI ViP MONITOR

Accessory for desk installation of the Mini hands-free monitor, ViP system. UV resistant.